

## Technical Data Sheet

Reference	Nordic Anti-Graffiti Coating
Purpose	A one pack breathable non-sacrificial coating giving excellent protection against fly poster and graffiti attack. The product allows easy repeated removal of graffiti by using water/detergent
Colour	Clear and Pigmented Liquid
Application	Apply by brush, roller, convention or airless spray.
Volume Solids	78% Matt; 78% Gloss; 48% Pigmented
Recommended Film Thickness	WFT 125 microns and DFT 95 microns
Coverage Rate	Theoretical 8 to 10 square metres/litre
Drying Time	Touch dry 3 / 4 hours; full cure 24 hours. Recoating (if required) time 3 to 4 hours
Thinners/Brushwash	Disposal
Weight Per Litre	.90-1.02
Flash Point	Above 64deg C.
V.O.C	50 grams per litre
Finish	Gloss – Semi Matt
Application Temperature	-5DegC +60DegC
Surface Preparation	All surfaces must be clean and dry, remove any soiling by power wash etc. Any soiling/graffiti apparent on painted surfaces i.e. masonry /rendered walls should be re-painted with good quality masonry exterior paint, prior to application.



Nordic Products and Services LTD |  
Church Road Stockton On Tees, TS18 2HN  
VAT: 09131544 | Company REG: 192434991