

Nordic Shadow Remover

NPSL's most powerful caustic mixture for the removal of the residual shadows left on brick, masonry and concrete after graffiti removal.

Description

Nordic Shadow Remover is our most powerful caustic mixture for the removal of the residual shadows left on brick, masonry and concrete after graffiti removal. It can also be used as a paint stripper. The shadow remover is formulated for use on vertical surfaces.

Application

Apply with a brick cleaning brush or alkali resistant brush and work well into the surface. Keep agitating with a brush and keep wet by applying more product if necessary. Do not allow to dry. Good rinsing is essential. Preferably use a high pressure, low volume water pump at 6.9 mPa at 18 to 25 litres per minute, 69 BAR at 18 to 25 litres per minute, 1000 p.s.i. at 4 to 5 imperial gallons per minute. Use a 15 to 45° fan tip. Water at up to 70°C may improve cleaning but is not essential.

If high pressure water is not available use low pressure and scrub whilst hosing.

IMPORTANT - PLEASE READ THE DATA SHEET FOR ALL SAFETY INFORMATION PRIOR TO USE

About Nordic Products and Services Ltd

Since 1994 Nordic have earned a reputation within the industry as the premier supplier of environmentally friendly graffiti cleaning products. Protection of the environment has always been of paramount importance to Nordic. Our policy of providing safe to use products has enabled Nordic to establish long term relationships with nationally recognised organisations, local authorities and contract service companies. Our technical sales and support team, product range and contract cleaning services provide the market with total graffiti removal and prevention solutions.